



NO FRICTION OIL

Rollers lubricant

Working instructions

- Pour NO FRICTION OIL directly on milling rollers that run without ink.
- Add product little by little, as rollers become drier.

Important

Before inking milling rollers treated with NO FRICTION OIL, wash them with solvent you normally use.

Main characteristics

- High protection on all kinds of rubbers
- Easy use

Safety

Read safety specifications before using product

Packing

Box 6 x 1 litre.

Storage

- Store at room temperature, in dry and well aired place.
- Keep far from heat and direct sun light.
- Keep closed the containers.
- Storage time: 24 months from production date.

Properties

Chemicals characteristics	Appearance	Viscous colourless liquid
	Flash point	> 100°C
	Density (25°C)	0,840 Kg/lt
	Organic Volatile Compound (VOC)	No VOC

Printing machine	Continuous form	v
	Rotary press <u>without</u> oven (Cold-set)	v
	Rotary press <u>with</u> oven (Heat-set)	v
	Sheet fed	v

The information given in this sheet is to be considered reliable and is provided in good faith but without guarantee. Subject to change without notice.



imaf S.p.A.

Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
Email: info@imaf.it - internet: www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643